

LxH [mm]	A_k [m ²]	V [m ³ /h]		Lw(A) [dB(A)]		Dp _s [Pa]	
		min	max	min	max	min	max
BLR-A60 400x400	0.0771	480	970	25	45	5	20
BLR-A60 600x400	0.1153	720	1450	25	45	5	20
BLR-A60 800x400	0.1535	960	1930	25	45	5	20
BLR-A60 1000x400	0.1917	1200	2410	25	45	5	20
BLR-A60 1200x400	0.2299	1440	2880	25	45	5	20
BLR-A60 1400x400	0.2681	1670	3360	25	45	5	20
BLR-A60 1600x400	0.3063	1910	3840	25	45	5	20
BLR-A60 1800x400	0.3445	2150	4320	25	45	5	20
BLR-A60 2000x400	0.3827	2390	4800	25	45	5	20
BLR-A60 400x500	0.1068	670	1340	25	45	5	20
BLR-A60 500x500	0.1335	830	1670	25	45	5	20
BLR-A60 600x500	0.1602	1000	2010	25	45	5	20
BLR-A60 800x500	0.2135	1330	2680	25	45	5	20
BLR-A60 1000x500	0.2669	1670	3350	25	45	5	20
BLR-A60 1200x500	0.3203	2000	4020	25	45	5	20
BLR-A60 1400x500	0.3736	2330	4690	25	45	5	20
BLR-A60 1600x500	0.4270	2670	5360	25	45	5	20
BLR-A60 1800x500	0.4804	3000	6030	25	45	5	20
BLR-A60 2000x500	0.5338	3330	6700	25	45	5	20
BLR-A60 400x600	0.1365	850	1710	25	45	5	20
BLR-A60 600x600	0.2050	1280	2570	25	45	5	20
BLR-A60 800x600	0.2735	1710	3430	25	45	5	20
BLR-A60 1000x600	0.3421	2140	4290	25	45	5	20
BLR-A60 1200x600	0.4106	2560	5150	25	45	5	20
BLR-A60 1400x600	0.4792	2990	6010	25	45	5	20
BLR-A60 1600x600	0.5477	3420	6870	25	45	5	20
BLR-A60 1800x600	0.6162	3850	7730	25	45	5	20
BLR-A60 2000x600	0.6848	4270	8590	25	45	5	20
BLR-A60 400x800	0.1958	1220	2460	25	45	5	20
BLR-A60 600x800	0.2947	1840	3700	25	45	5	20
BLR-A60 800x800	0.3936	2460	4940	25	45	5	20
BLR-A60 1000x800	0.4924	3070	6180	25	45	5	20
BLR-A60 1200x800	0.5913	3690	7420	25	45	5	20
BLR-A60 1400x800	0.6902	4310	8660	25	45	5	20
BLR-A60 1600x800	0.7890	4920	9900	25	45	5	20
BLR-A60 1800x800	0.8879	5540	11140	25	45	5	20
BLR-A60 2000x800	0.9868	6160	12380	25	45	5	20
BLR-A60 400x1000	0.2552	1590	3200	25	45	5	20
BLR-A60 600x1000	0.3844	2400	4820	25	45	5	20
BLR-A60 800x1000	0.5136	3210	6440	25	45	5	20
BLR-A60 1000x1000	0.6428	4010	8070	25	45	5	20
BLR-A60 1200x1000	0.7720	4820	9690	25	45	5	20
BLR-A60 1400x1000	0.9012	5620	11310	25	45	5	20
BLR-A60 1600x1000	1.0304	6430	12930	25	45	5	20
BLR-A60 1800x1000	1.1596	7240	14550	25	45	5	20
BLR-A60 2000x1000	1.2888	8040	16170	25	45	5	20

1. oldal



2040 Budaörs Gyár utca 2.
BITEP Ipari park



info@cairox.hu



+36 23 44 41 33

LxH [mm]	A_k [m ²]	V [m ³ /h]		Lw(A) [dB(A)]		Dp _s [Pa]	
		min	max	min	max	min	max
BLR-A60 400x1200	0.3146	1960	3950	25	45	5	20
BLR-A60 600x1200	0.4741	2960	5950	25	45	5	20
BLR-A60 800x1200	0.6336	3950	7950	25	45	5	20
BLR-A60 1000x1200	0.7932	4950	9950	25	45	5	20
BLR-A60 1200x1200	0.9527	5950	11950	25	45	5	20
BLR-A60 1400x1200	1.1122	6940	13950	25	45	5	20
BLR-A60 1600x1200	1.2718	7940	15960	25	45	5	20
BLR-A60 1800x1200	1.4313	8930	17960	25	45	5	20
BLR-A60 2000x1200	1.5908	9930	19960	25	45	5	20
BLR-A60 400x1500	0.4036	2520	5060	25	45	5	20
BLR-A60 600x1500	0.6086	3800	7640	25	45	5	20
BLR-A60 800x1500	0.8137	5080	10210	25	45	5	20
BLR-A60 1000x1500	1.0187	6360	12780	25	45	5	20
BLR-A60 1200x1500	1.2237	7640	15350	25	45	5	20
BLR-A60 1400x1500	1.4288	8920	17930	25	45	5	20
BLR-A60 1600x1500	1.6338	10200	20500	25	45	5	20
BLR-A60 1800x1500	1.8388	11480	23070	25	45	5	20
BLR-A60 2000x1500	2.0439	12760	25640	25	45	5	20
BLR-A60 2000x1600	2.1949	13700	27540	25	45	5	20
BLR-A60 2000x2000	2.7989	17470	35120	25	45	5	20

LxH = Névleges L (szélesség) és H (magasság) [mm]

A_k = Effektív keresztmetszet [m²]

V = Levegőmennyiség [m³/h]

Lw(A) = Hangteljesítmény szint [dB(A)]

Dp_s = Statikus nyomásvesztés a rácson [Pa]

A fenti adatok izotermikus légállapot mellett értendők!

